


HYDRAULIC BREAKERS (HAMMERS)



Mini-Machine Mount



FEATURES INCLUDE

- 3 year warranty
- Mono-block design / no tie rods
- Anti-blank firing system hydraulic brake
- No re-gassing needed
- Only 2 internal moving parts
- 2 speed control / variable stroke
- Quiet Operation
- Self-regulating
- Body bushings around piston



Skid Steer Mount



Excavator Mount



Our 5 year quest to develop a superior hydraulic breaker is now available from Blue Diamond®. This “hammer” design offers technology, simplicity, reliability, ease of setup, and service support. No more downtime, get started on your demolition, construction, and quarry jobs now.

PART NUMBER	MODEL	WORKING PRESSURE	MAX OIL FLOW	FREQUENCY (BPM)	OPERATING WEIGHT	TOOL DIAMETER	ENERGY CLASS	CARRIER WEIGHT	(PSI) BACK PRESSURE
135005	HB50	1,750	7	1,200	132 LBS	1.5	100	1,500-2,650 LBS	290-360
135009	HB95		11		220 LBS	1.8	200	2,650-4,000 LBS	
135016	HB165		13		370 LBS	2.2	400	4,000-6,600 LBS	
135021	HB210		16	1,100	463 LBS	2.5	500	6,100-9,900 LBS	
135030	HB300		21.2		661 LBS	2.9	700	8,800-15,500 LBS	
135040	HB400		29.2	900	882 LBS	3.1	1,000	13,500-20,900 LBS	
135053	HB530	32	1,169 LBS		3.3	1,200	17,650-25,350 LBS		
135095	HB950	34	2,161 LBS		4	2,000	22,000-33,000 LBS		
135098	HB1400	2,050	37	600-800	2,976 LBS	4.6	3,000	30,000-50,000 LBS	145
135100	HB1800		53	490-630	3,968 LBS	5.4	4,000	48,000-70,000 LBS	
135105	HB2500	2,200	61	460-630	5,291 LBS	6	5,000	60,000-80,000 LBS	
135110	HB3000	2,350	75	380-500	6,614 LBS	6.5	7,000	70,000-110,000 LBS	

