

MINI BUCKET

LOW PROFILE

Blue Diamond® Mini Skid Steer Low Profile

Buckets is built from 3/16" A36 steel for dependable digging, loading, grading, back dragging, and material handling. Available in 36" to 60" widths with 15" or 20" back heights, its low-profile design and 25" bottom depth provide excellent cutting-edge visibility while reinforced bottom wear plates add durability in high-contact areas.

Choose from smooth or tooth configurations, with optional bolt-on cutting edges available for additional wear protection. A 70° back angle provides excellent rollback and dump performance, and all buckets come standard with a D-ring. Mini Universal mounts are available throughout the lineup, with select models offered for Bobcat MT machines.

15" or 20" Tall

70° Back Angle for great rollback and dump angle

25" Deep, Front to Back

Reinforced Bottom 3/8" Wear Bars

PART NO.	107850-25	107855-25	107860-25
MODEL	36" HD W/20" BACK	44" HD W/20" BACK	52" HD W/20" BACK
STRUCK CAP.	6.14 CU FT	7.50 CU FT	8.87 CU FT
WEIGHT	509 LBS	480 LBS	600 LBS

PART NO.	108010-25	108015-25	108020-25	108025-25	108030-25
MODEL	36" SMOOTH W/15" BACK	36" TOOTH W/15" BACK	42" SMOOTH W/15" BACK	42" TOOTH W/15" BACK	44" SMOOTH W/15" BACK
BACK HEIGHT	15" BACK	15" BACK	15" BACK	15" BACK	15" BACK
STRUCK CAP.	4.43 CU FT	4.43 CU FT	5.17 CU FT	5.17 CU FT	5.42 CU FT
WEIGHT	385 LBS	426 LBS	448 LBS	509 LBS	480 LBS

PART NO.	108031-25	108040-25	108045-25	108060-25	108065-25
MODEL	44" TOOTH W/15" BACK	48" SMOOTH W/15" BACK	48" TOOTH W/15" BACK	52" SMOOTH W/15" BACK	52" TOOTH W/15" BACK
BACK HEIGHT	15" BACK	15" BACK	15" BACK	15" BACK	15" BACK
STRUCK CAP.	5.42 CU FT	5.91 CU FT	5.91 CU FT	6 CU FT	6 CU FT
WEIGHT	600 LBS	600 LBS	385 LBS	426 LBS	448 LBS

PART NO.	108012-25	108012-26	108017-25	108022-25	108027-25	108032-25	108032-26	108037-25	108037-26	108042-25	108047-25	108062-25	108062-26	108067-25	108090-25
MODEL	36" SMOOTH	36" SMOOTH	36" TOOTH	42" SMOOTH	42" TOOTH	44" SMOOTH	44" SMOOTH	44" TOOTH	44" TOOTH	48" SMOOTH	48" TOOTH	52" SMOOTH	52" SMOOTH	52" TOOTH	60" SMOOTH
BACK HT.	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK	20" BACK
STRUCK CAPACITY	6.14 CU FT	6.14 CU FT	6.14 CU FT	7.16 CU FT	7.16 CU FT	7.50 CU FT	7.50 CU FT	7.50 CU FT	7.50 CU FT	8.19 CU FT	8.19 CU FT	8.87 CU FT	8.87 CU FT	8.87 CU FT	6.83 CU FT
WEIGHT	249 LBS	249 LBS	250 LBS	269 LBS	279 LBS	275 LBS	246 LBS	285 LBS	247 LBS	310 LBS	320 LBS	350 LBS	300 LBS	360 LBS	334 LBS

KEY FEATURES

- ◆ Bucket widths from 36" to 60"
- ◆ Available with 15" or 20" back heights
- ◆ Compact 25" bottom depth
- ◆ Bucket wrap and sides constructed from 3/16" A36 steel
- ◆ Smooth or tooth configurations
- ◆ Low-profile design improves operator visibility
- ◆ Designed for effective back dragging with the bucket heel
- ◆ Standard D-ring
- ◆ Smooth models feature a 1/2" x 4" cutting edge punched for optional bolt-on edges
- ◆ Tooth models feature heavy-duty 230-series replaceable cast teeth
- ◆ Durable powder-coated finish
- ◆ Recommended for mini skid steers under 45 HP
- ◆ Mini Universal and select models have Bobcat MT mounts