

# COLD PLANER

## EXTREME DUTY SERIES 2

This premium Blue Diamond® self-leveling Extreme Duty Series 2 Cold Planer is designed for removing the entire layer of asphalt or cement in preparation for trenching or for milling deteriorated sections for later resurfacing. Created to mill pre-set sections on hard and compact surfaces such as asphalt and cement, they allow the possibility to reuse milled material for backfilling trenches.

Thanks to the self-levelling system on the working surface, a constant milling depth is guaranteed under all conditions. The side slides of the road planer automatically align themselves to the milling surface on which they rest, providing maximum stability.




### APPLICATIONS INCLUDE:

- Removing asphalt surfaces prior to overlay
- Widening shoulders
- Repairing potholes
- Restoring drainage lines
- Mixing stabilizing agents into base for a more durable repair

### FEATURES INCLUDE:

- 14" to 48" grinding widths
- 4.3" to 6.7" cutting depths
- Independant depth adjustment on right or left
- Milled material remains in work area
- Floating transverse tilt with damper
- Electronic side shift
- Self-leveling system - constant planing depth
- Hydraulic motor in direct drive with the drum
- Cut and depth indicators
- Optional water kit and drum options available



Cut and depth indicators



Self-leveling system



Water kit available

| PART NUMBER | MODEL                                       | CUTTING DEPTH | MIN-MAX FLOW | MAX PRESSURE | TILT DEGREES | WEIGHT*   |
|-------------|---|---------------|--------------|--------------|--------------|-----------|
| 160950      | 14" Extreme Duty Series 2, Low Flow         | 4.3"          | 12-21 GPM    | 3,625 PSI    | 16°          | 1,350 lbs |
| 160951      | 16" Extreme Duty Series 2, Low Flow         | 5.9"          | 17-30 GPM    | 3,625 PSI    | 16°          | 1,450 lbs |
| 160952      | 18" Extreme Duty Series 2, High Flow        | 6.7"          | 27-40 GPM    | 4,500 PSI    | 16°          | 1,900 lbs |
| 160953      | 20" Extreme Duty Series 2, High Flow        | 6.7"          | 27-40 GPM    | 4,500 PSI    | 16°          | 2,000 lbs |
| 160954      | 24" Extreme Duty Series 2, High Flow        | 6.7"          | 27-40 GPM    | 4,500 PSI    | 16°          | 2,100 lbs |
| 160955      | 30" Extreme Duty Series 2, High Flow        | 6.7"          | 29-45 GPM    | 4,500 PSI    | 16°          | 2,300 lbs |
| 160956      | 40" Extreme Duty Series 2, High Flow        | 5"            | 29-50 GPM    | 4,500 PSI    | 16°          | 2,400 lbs |
| 160957      | 48" Extreme Duty Series 2, High Flow        | 5"            | 32-50 GPM    | 4,500 PSI    | 16°          | 2,660 lbs |
| 360602      | Extreme Duty Series 2 Pressurized Water Kit | —             | —            | —            | —            | 70 lbs    |

