

EXCAVATOR DRUM MULCHER

EXTREME DUTY



The Blue Diamond® Extreme Duty Excavator Drum Mulcher is one of the fastest ways to tear down a forest. Turn trees to wood chips in minutes using our durable drum mulcher built with high strength steel.

No job is too big or small with cutting widths up to 50 inches. All our drum rotors have fixed teeth set in helical position with “p-cut” depth limiters. Choose the reversible carbide teeth option for maximum tooth lifespan when working in rocky areas! And with centralized grease points and hydraulic quick couplers, you can trust that routine maintenance is straightforward and easy.

The Extreme Duty model comes with a double row of chains to keep material flowing and shield the operator from thrown debris. centralized grease points and hydraulic quick couplers, you can trust that routine maintenance is straightforward and easy.

APPLICATIONS INCLUDE:

- Land Clearing
- Vegetation Management
- Right-of-way Maintenance
- Agricultural Property Upkeep
- Stump Removal
- Forestry Applications

High Strength Steel

7" Cutting Diameter

Two Rows of Chains

Fixed Teeth w/ Bite Limiters

Wear Resistant Steel Skids



KEY FEATURES

- ◆ 24,000 to 37,000 lb Excavator Size
- ◆ Available in 40" and 50" cutting widths
- ◆ Variable Displacement (55 - 85cc Bosch Rexroth)
- ◆ Recommended Flow is 32-45 GPM
- ◆ 7" diameter cutting capacity
- ◆ Required pressure 4,000-5,500 PSI
- ◆ Chain curtain minimizes discharge
- ◆ Hydraulic front cover
- ◆ Brush rake option is available
- ◆ Requires case drain, hoses & couplers



Hydraulic adjustable door



Labeled hose & grease ports



Bite limiters

PART NO.	390555	390565	190551
MODEL	40" EXTREME DUTY W/CARBIDE TEETH	50" EXTREME DUTY W/CARBIDE TEETH	SEVERE & EXTREME DUTY BRUSH RAKE OPTION
MOTOR SIZE	50-85 CC	50-85 CC	—
HOST MACHINE	FITS 24K-37K MACHINES	FITS 24K-37K MACHINES	—
MIN-MAX FLOW	32-45 GPM	32-45 GPM	—
WEIGHT*	1,500 LBS	1,665 LBS	625 LBS

*Weight is without mount. Excavator Drum Mulchers do not come with hoses or couplers. Host machine requires case drain and may require additional hydraulic valve for aux flow. All these items are dealer responsible for time and materials. Manufacturer suggested time (MST) is 1-hour shop required to tune the mulcher to the host machine, and this time excludes all other dealer installed service items. Ask your sales rep. for detailed installation instructions.

Revised: 04.08.26



BLUEDIAMONDATTACHMENTS.COM

4512 Anderson Rd. | Knoxville TN 37918

888-376-7027