

# POWER RAKE EXTREME DUTY



High-Torque Geroler Motor

4" x 4" Heavy Duty Square Tube for Superior Strength

6-3/4" Drum Diameter

Adjustable Material Bar


No-Flat Airless Wheels



When productivity matters, look no further. Travel faster, cut deeper, and move on to the next job with the Blue Diamond® Extreme Duty Power Rake. With skid steer machine sizes increasing across the industry, there's a growing demand for more powerful and durable power rake / soil conditioner attachments. The **Blue Diamond® Extreme Duty Power Rake** is purpose-built to power through jobs where others fail while offering easy servicing and exceptional longevity.

## KEY FEATURES

- ◆ Available in 72" to 96" working widths
- ◆ 1.5" spindle on castors with spacers for smoother operation and greater durability
- ◆ 1" front wheel axles—stronger than competitive 3/4" designs
- ◆ 1.5" motor shaft with high-pressure seals for maximum motor protection
- ◆ 5-position, 20° adjustable angle available in manual or hydraulic configurations
- ◆ 6 3/4" drum diameter (10 3/4" including teeth) for optimal ground engagement
- ◆ Replaceable teeth hardened to HRC 50 for long wear life
- ◆ Double struts on castors for added stability and strength



Side plate



Airless tires - NO flats



Bolt-on skid shoes

PART NO.	332110	332111	332112	332113	332114	332115	332116	332117	332118	332119	332120	332121
MODEL	72" W/FIXED STEEL TEETH & SKID STEER MOUNT	72" W/ FIXED STEEL TEETH & SKID STEER MOUNT	72" W/ REPLACEABLE CARBIDE TEETH & SKID STEER MOUNT	72" W/ REPLACEABLE CARBIDE TEETH & SKID STEER MOUNT	84" W/FIXED STEEL TEETH & SKID STEER MOUNT	84" W/FIXED STEEL TEETH & SKID STEER MOUNT	84" W/ REPLACEABLE CARBIDE TEETH & SKID STEER MOUNT	84" W/ REPLACEABLE CARBIDE TEETH & SKID STEER MOUNT	96" W/ FIXED STEEL TEETH & SKID STEER MOUNT	96" W/ FIXED STEEL TEETH & SKID STEER MOUNT	96" W/ REPLACEABLE CARBIDE TEETH & SKID STEER MOUNT	96" W/ REPLACEABLE CARBIDE TEETH & SKID STEER MOUNT
FLOW RANGE	15-26 GPM	15-26 GPM	15-26 GPM	15-26 GPM	15-26 GPM	15-26 GPM	15-26 GPM	15-26 GPM	15-26 GPM	15-26 GPM	15-26 GPM	15-26 GPM
MANUAL OR HYDRAULIC ANGLE	MANUAL ANGLE	HYDRAULIC ANGLE	MANUAL ANGLE	HYDRAULIC ANGLE	MANUAL ANGLE	HYDRAULIC ANGLE	MANUAL ANGLE	HYDRAULIC ANGLE	MANUAL ANGLE	HYDRAULIC ANGLE	MANUAL ANGLE	HYDRAULIC ANGLE
WEIGHT	1,134 LBS	1,192 LBS	1,184 LBS	1,242 LBS	1,159 LBS	1,217 LBS	1,209 LBS	1,267 LBS	1,185 LBS	1,205 LBS	1,032 LBS	1,052 LBS

Skid Shoes, Universal Wiring Harness, and Case Drain Hose Kit Included, 1/2" Hose Couplers Standard. Full angled widths are estimated about 10"-12" less. See table below for OEM optional wiring harnesses. Recommended flow is 15-26 GPM.

