



# POWER RAKE

## EXTREME DUTY WITH 3-POINT HITCH



Built for 35–75 HP tractors with Category 2, 3-point hitches, the **Blue Diamond® Extreme Duty Power Rake** is the ultimate land preparation tool. Available in 72” to 96” widths, it adapts to projects of all sizes.

Whether you call it a power rake or a Harley rake, these PTO-driven tractor attachments are built to efficiently rake and windrow rocks, soil, and debris—making them perfect for seedbed preparation, land leveling, and jobsite cleanup.

Choose between carbide-tipped weld-on teeth or replaceable carbide-tipped teeth and select manual or hydraulic angle configurations to match your needs. Proudly made in the USA, this attachment delivers durability, precision engineering, and the superior support you expect from Blue Diamond Attachments.

60 HP PTO Gearbox

4” x 4” Heavy Duty Square Tube for Superior Strength



8” Drum Diameter

No-Flat Airless Wheels

### KEY FEATURES

- ◆ Drum widths: 72”, 84”, and 96”
- ◆ Recommended for 30-75 HP tractors
- ◆ 8” diameter drum with 1.5” teeth
- ◆ Chain drive unit for increased torque
- ◆ 1-1/2” Drive Shaft
- ◆ 1.25” spindles with 1” adjustable height spacers
- ◆ 60 HP PTO Gearbox
- ◆ 72” (Angle Width 69” @ 10°, 66” @ 20°)
- ◆ 84” (Angle Width 81” @ 10°, 78” @ 20°)
- ◆ 96” (Angle Width 93” @ 10°, 90” @ 20°)
- ◆ Optional Hydraulic Angle Kit
- ◆ Teeth: Carbide Weld-On or Replaceable Teeth



Optional skid shoes



Airless tires - NO flats



3/8” side shields and PTO Shaft

PART NO.	432105	432110	432115	432117	132050	332735	332740
MODEL	72” W/ REPLACEABLE CARBIDE TEETH & 3-POINT HITCH MOUNT	84” W/ REPLACEABLE CARBIDE TEETH & 3-POINT HITCH MOUNT	96” W/ REPLACEABLE CARBIDE TEETH & 3-POINT HITCH MOUNT	96” W/ FIXED STEEL TEETH & 3-POINT HITCH MOUNT	OPTIONAL SKID SHOES WITH HARDWARE	OPTIONAL EXTREME DUTY HYDRAULIC ANGLE KIT W/60” HOSE	OPTIONAL EXTREME DUTY HYDRAULIC ANGLE KIT W/84” HOSE
HORSEPOWER	35-75 HP	35-75 HP	35-75 HP	35-75 HP	—	—	—
3-POINT HITCH FITS	CATAGORY 2	CATAGORY 2	CATAGORY 2	CATAGORY 2	—	—	—
WEIGHT	1,217 LBS	1,024 LBS	1,685 LBS	1,310 LBS	30 LBS	25 LBS	25 LBS

*Extreme Duty - fits CAT 2 & 3 pt hitch. High torque, optional replaceable teeth, requires hoses or hydraulic angle kit, larger model, protected bearings. Optional fixed harden steel (232111) or carbide teeth that are either replaceable (232118) or fixed (232112). Anything over 3,500 PSI requires a case drain.*

