

POWER RAKE STANDARD DUTY



FEATURES INCLUDE

- Flip up wheels
- No-flat airless wheels
- Drum width 48", 60" and 72"
- 5/8" greaseable axles on wheels
- 7" diameter drum with 1.5" teeth
- Overall width 12" more than drum width
- 1.25" spindles with adjustable height
- Bolt-on mount (can be switched for a different mini or full size skid steer mount)
- Spindles on drum are 1 3/8" diameter greaseable bearings
- Fixed carbide teeth
- Available with manual or hydraulic angle

This lighter unit is suited to smaller frame skid steers and walk behind machines. The bolt-on mount allows greater flexibility for rental companies and dealers to have the correct model for the right machine, with mounts offered for mini and full size skid steer machines.



Reversible side shield



Flip up wheels



Heavy duty protected bearing

PART NUMBER ¹	MODEL	WORKING WIDTH (STRAIGHT)	WORKING WIDTH (ANGLED) 10°/20°	OVERALL WIDTH (STRAIGHT)	WEIGHT ²
332450	48" w/Fixed Mount	48"	—	60"	550 lbs
332451	48" w/Manual Angle Mount	48"	46"/44"	60"	600 lbs
332452	48" w/Hydraulic Angle Mount	48"	46"/44"	60"	625 lbs
332453	60" w/Fixed Mount	60"	—	72"	600 lbs
332454	60" w/Manual Angle Mount	60"	58"/56"	72"	650 lbs
332455	60" w/Hydraulic Angle Mount	60"	58"/56"	72"	675 lbs
332456	72" w/Fixed Mount	72"	—	84"	700 lbs
332457	72" w/Manual Angle Mount	72"	70"/68"	84"	750 lbs
332458	72" w/Hydraulic Angle Mount	72"	70"/68"	84"	775 lbs

1 — Add -25 for Mini Universal Mount and add -26 for Bobcat MT Mount. 2 — Weight varies on mount.

888-376-7027

info@bluediamondattachments.com

BlueDiamondAttachments.com

888-377-7027

4512 Anderson Rd., Knoxville, TN 37918

Monday - Friday, 8am - 5pm EST

Revised: 03.28.25

