

ROAD SAW EXTREME DUTY

Blue Diamond® Extreme Duty Road Saws

deliver unmatched efficiency for trenching in asphalt, concrete, and rock. Designed with hydraulic depth control, side shift, and built-in trench clearing, these attachments cut cleaner, faster, and more accurately than traditional methods. Designed for cutting asphalt and soil trenching, our skid steer road wheel saws offer cutting depths up to 17 or 24 inches!

From utility installation and roadwork to fiber optic projects, Blue Diamond® Extreme Duty Road Saws offer the flexibility and performance contractors need for dependable trenching in any environment.

Hydraulic
Scraper Blade

Hydraulic
Depth
Adjustment

Hydraulic
Side Shift

Trench
Clearing
Blade

Removable
Tooth Plate Kits

Skid Shoe



Hydraulic scraper blade




Material flow diverter



Predrilled holes for optional
water tank



Depth gauge provides
uniform depth for cut control



Hydraulic side shift 0" — 26"



Removable tooth plate kits,
cutting widths from 2" to 8"

KEY FEATURES

- ♦ Saw discs feature removable tooth plate kits with cutting widths from 2" to 8"
- ♦ Recommend hydraulic flow: 21 — 42 GPM
- ♦ Hydraulic Side shift: 0 to 26 inches
- ♦ Hydraulic depth adjustment
- ♦ Trench clearing blade
- ♦ Water Kit Available
- ♦ Universal Skid Steer Mount

PART NUMBER	361120	361121	361122	361123	361124	361125	361130	361131	361132	361133	361134
OVERALL DIMENSIONS	75"L X 65"H X 68 1/2"W						84"L X 76"H X 68 1/2"W				
CUTTING DEPTH	6" — 17"						8" — 24"				
CUTTING WIDTH	2"	3 1/4"	4"	5"	6 1/4"	8"	3 1/4"	4"	5"	6 1/4"	8"
OPERATING PRESSURE	2320 — 4350 PSI						2320 — 4350 PSI				
MIN-MAX FLOW	21 — 42 GPM						24 — 42 GPM				
DRUM SPEED	55 — 110 RPM						55 — 95 RPM				
MAX HYDRAULIC MOTOR POWER	65 HP						65 HP				
WEIGHT*	2,300 LBS	2,350 LBS	2,375 LBS	2,400 LBS	2,450 LBS	2,500 LBS	2,850 LBS	2,875 LBS	2,900 LBS	2,950 LBS	3,000 LBS

* Weight is for the unit only.

Revised: 10.29.25



BLUEDIAMONDATTACHMENTS.COM

4512 Anderson Rd. | Knoxville TN 37918

888-376-7027