

TRENCHER MINI

The Blue Diamond® Mini Trencher was designed specifically for mini skid steers and loaders, the Blue Diamond® Mini Series Trenchers offer a 36" cutting depth, adjustable depth control system, extended auger, and a self-adjusting crumber. Combo, dirt, and rock chain options with 4" to 8" cutting widths.


Eaton Drive Motor

Adjustable Skid Foot

Extended Auger

Combo Chain w/Rock & Dirt Chain Options


Spring-loaded Crumber



Extended auger removes debris



Adjustable foot keeps trench depth constant



Self-adjusting crumber sweeps the trench clean

KEY FEATURES

- ◆ **Chain Styles:** Dirt, Combo, and Rock for different soil conditions
- ◆ **Manual Sideshift Mount:** Allows precise trench positioning
- ◆ **High-Torque Drive:** Bell Eaton motor with planetary drive for maximum power
- ◆ **Hoses, Crumber, and Couplers:** Included
- ◆ **Mounts:** Mini Uni (Fixed) & Bobcat MT (Sideshift)

CUTTING WIDTH	4"	4"	4"	4"	6"	6"	6"	6"	8"	8"	8"	8"
PART NUMBER	131503-25	331503-26	131500-25	131506-25	131504-25	331504-26	131501-25	131507-25	131505-25	331505-26	131502-25	131502-25
CUTTING DEPTH	UP TO 36"	UP TO 36"	UP TO 36"	UP TO 36"	UP TO 36"	UP TO 36"	UP TO 36"	UP TO 36"	UP TO 36"	UP TO 36"	UP TO 36"	UP TO 36"
CHAIN	COMBO	COMBO	DIRT	ROCK	COMBO	COMBO	DIRT	ROCK	COMBO	COMBO	DIRT	ROCK
MOUNT	MINI UNI	BOBCAT MT	MINI UNI	MINI UNI	MINI UNI	BOBCAT MT	MINI UNI	MINI UNI	MINI UNI	BOBCAT MT	MINI UNI	MINI UNI
FOOT DEPTH PRESETS	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"	24" / 30" / 36"
RECOMMENDED FLOW	10-25 GPM	10-25 GPM	10-25 GPM	13-25 GPM	10-25 GPM	10-25 GPM	10-25 GPM	10-25 GPM	10-25 GPM	10-25 GPM	10-25 GPM	10-25 GPM
MOTOR TYPE	2K BELL EATON	2K BELL EATON	2K BELL EATON	2K BELL EATON	2K BELL EATON	2K BELL EATON	2K BELL EATON	2K BELL EATON	2K BELL EATON	2K BELL EATON	2K BELL EATON	2K BELL EATON
MAX PRESSURE	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM	3,500 PSI @ 16 GPM
MAX FLOW	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI	25 GPM @ 2,900 PSI
MAX CONTINUOUS POWER	34 HP	34 HP	34 HP	34 HP	34 HP	34 HP	34 HP	34 HP	34 HP	34 HP	34 HP	34 HP
DIMENSIONS	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W	76"L X 26"H X 48"W
WEIGHT	320 LBS	320 LBS	320 LBS	320 LBS	320 LBS	320 LBS	320 LBS	320 LBS	320 LBS	320 LBS	320 LBS	320 LBS